

DC-Micromotors

Precious Metal Commutation

10 mNm
8,5 W

Series 2232 ... SR

Values at 22°C and nominal voltage	2232 U	006 SR	009 SR	012 SR	015 SR	018 SR	024 SR		
1 Nominal voltage	U_N	6	9	12	15	18	24	V	
2 Terminal resistance	R	0,81	2,14	4,09	6,61	9,04	16,4	Ω	
3 Output power	$P_{2nom.}$	11	9,35	8,7	8,41	8,86	8,68	W	
4 Efficiency, max.	$\eta_{max.}$	87	86	86	85	86	86	%	
5 No-load speed	n_0	7 100	7 400	7 100	7 100	7 100	7 100	min ⁻¹	
6 No-load current, typ. (with shaft \varnothing 2 mm)	I_0	0,035	0,0241	0,0175	0,0139	0,0116	0,0087	A	
7 Stall torque	M_H	59,2	48,3	46,8	45,2	47,6	46,7	mNm	
8 Friction torque	M_R	0,28	0,28	0,28	0,28	0,28	0,28	mNm	
9 Speed constant	k_n	1 190	827	595	476	397	298	min ⁻¹ /V	
10 Back-EMF constant	k_E	0,84	1,21	1,68	2,1	2,52	3,36	mV/min ⁻¹	
11 Torque constant	k_M	8,03	11,5	16	20,1	24,1	32,1	mNm/A	
12 Current constant	k_I	0,125	0,087	0,062	0,05	0,042	0,031	A/mNm	
13 Slope of n-M curve	$\Delta n/\Delta M$	120	153	152	157	149	152	min ⁻¹ /mNm	
14 Rotor inductance	L	45	90	180	280	400	710	μ H	
15 Mechanical time constant	τ_m	6	6	6	6	6	6	ms	
16 Rotor inertia	J	4,8	3,8	3,8	3,8	3,8	3,8	gcm ²	
17 Angular acceleration	$\alpha_{max.}$	120	120	120	120	120	120	$\cdot 10^3$ rad/s ²	
18 Thermal resistance	R_{th1} / R_{th2}	4 / 13						K/W	
19 Thermal time constant	τ_{w1} / τ_{w2}	7 / 340						s	
20 Operating temperature range:									
– motor		-30 ... +85 (optional version -55 ... +125)							°C
– winding, max. permissible		+125							°C
21 Shaft bearings		sintered bearings (standard)			ball bearings, preloaded (optional version)				
22 Shaft load max.:									
– with shaft diameter		2			2				mm
– radial at 3 000 min ⁻¹ (3 mm from bearing)		1,5			8				N
– axial at 3 000 min ⁻¹		0,2			0,8				N
– axial at standstill		20			10				N
23 Shaft play:									
– radial	\leq	0,03			0,015				mm
– axial	\leq	0,2			0				mm
24 Housing material		steel, black coated							
25 Mass		62						g	
26 Direction of rotation		clockwise, viewed from the front face							
27 Speed up to	$n_{max.}$	8 000						min ⁻¹	
28 Number of pole pairs		1							
29 Magnet material		NdFeB							
Rated values for continuous operation									
30 Rated torque	M_N	10	10	10	10	10	10	mNm	
31 Rated current (thermal limit)	I_N	1,3	0,93	0,67	0,53	0,44	0,33	A	
32 Rated speed	n_N	5 900	5 810	5 510	5 420	5 530	5 490	min ⁻¹	

Note: Rated values are calculated with nominal voltage and at a 22°C ambient temperature. The R_{th2} value has been reduced by 0%.

Note:

The diagram indicates the recommended speed in relation to the available torque at the output shaft for a given ambient temperature of 22°C.

The diagram shows the motor in a completely insulated as well as thermally coupled condition (R_{th2} 50% reduced).

The nominal voltage (U_N) curve shows the operating point at nominal voltage in the insulated and thermally coupled condition. Any points of operation above the curve at nominal voltage will require a higher operating voltage. Any points below the nominal voltage curve will require less voltage.



