



## REV-Q703

- > Qseven 2.0 Evaluation Baseboard (Mini ITX )
- > 1x DP/ HDMI/ LVDS
- > 1x COM
- > 7x USB
- > 1x Ethernet
- > 1x mPCIe x1 (with SIM Socket)
- > 1x PCIe x1
- > 2x SATA
- > 1x SD card slot
- > Audio Phone Jack(Line In, Line out, Mic-in)
- > 1x Onboard Accelerometer (Freescale MMA8451Q)
- > 16Bit GPIO by TCA9555

### + Spec

System	
<b>Other</b>	Onboard Accelerometer (Freescale MMA8451Q)
I/O	
<b>External I/O Connector</b>	1 x USB 2.0 1 x USB 3.0 1 x Ethernet 1 x HDMI 1 x COM 1 x DP 1 x OTG 1 x SD socket 3 x Audio phone jack
<b>Internal I/O Connector</b>	2 x USB2.0 (5x2) Header 1 x USB 2.0 (5x1) wafer box 1 x GPIO(10x2) Header 1 x PCIe x1 1 x mPCIe x1 (with SIM Socket) 2 x SATA w/ PWR 1 x SPI 1 x CAN 1 x LPC 1 x JFP (Miscellaneous Setting Connector) 1 x PWM CPU Fan (4x1) Header 1 x 4P PWR Header 1 x LVDS connector 1 x Back light connector
Audio	
<b>Chipset</b>	X86 platform => ALC892 ARM platform => WM8962
<b>Audio Interface</b>	Line out/Line in/MIC in interface (I2C/ I2S/ HDA switch onboard for different Audio codec)
Mechanical & Environmental	
<b>Power Requirement</b>	12V DC
<b>Operating Temp</b>	-40°C ~ 85°C
<b>Storage Temp</b>	-40°C ~ 85°C
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Dimension (L x W)</b>	170 x 170mm
<b>Weight</b>	TBD

### + Ordering

REV-Q703A1R01